

864 Text Message

Functional Group ID= **TX**

Introduction:

This standard provides the format and establishes the data contents of a text transaction set. The text transaction set provides users with a capability to electronically move messages, contracts, explanations and other one-time communications. It is the intent of this transaction set to provide electronic communication (messages) for people, not for computer processing. The use of the transaction set to transmit quasi or unique transaction set standards is discouraged. The use of the text transaction set demands of the sender certain detailed information about the recipient. The transaction set's purpose is to provide communication to the recipient in some human-readable form. The recipient's network will dictate what capabilities are available for delivery of the information. It is the responsibility of the sender to obtain this information and include it in the transmission.

Notes:

For the purpose of Y2K compliancy, all dates will employ a bridging (windowing or 49/50 rule) application. Bridging is a technique in which a date of 00 - 49 is considered to reference the year 2000, and a year of 50 - 99 is considered to reference the 1900 year.

Heading:

	<u>Pos. No.</u>	<u>Seg. ID</u>	<u>Name</u>	<u>Req. Des.</u>	<u>Max.Use</u>	<u>Loop Repeat</u>	<u>Notes and Comments</u>
Must Use	010	ST	Transaction Set Header	M	1		
Must Use	020	BMG	Beginning Segment For Text Message	M	1		
	030	DTM	Date/Time/Period	O	10		
LOOP ID - N1						200	
	040	N1	Name	O	1		
Not Used	050	N2	Additional Name Information	O	2		
	060	N3	Address Information	O	2		
Not Used	070	N4	Geographic Location	O	1		
Must Use	080	REF	Reference Numbers	O	12		
	090	PER	Administrative Communications Contact	O	3		

Detail:

	<u>Pos. No.</u>	<u>Seg. ID</u>	<u>Name</u>	<u>Req. Des.</u>	<u>Max.Use</u>	<u>Loop Repeat</u>	<u>Notes and Comments</u>
LOOP ID - MIT						200	
Must Use	010	MIT	Message Identification	M	1		
LOOP ID - N1						200	
Not Used	020	N1	Name	O	1		
Not Used	030	N2	Additional Name Information	O	2		

864 - Text Message

Not Used	040	N3	Address Information	O	2	
Not Used	050	N4	Geographic Location	O	1	
Not Used	060	REF	Reference Numbers	O	12	
Not Used	070	PER	Administrative Communications Contact	O	3	
Must Use	080	MSG	Message Text	M	100000	

Summary:

	Pos. No.	Seg. ID	Name	Req. Des.	Max.Use	Loop Repeat	Notes and Comments
Must Use	010	SE	Transaction Set Trailer	M	1		

Segment: **ST** Transaction Set Header
Position: 010
Loop:
Level: Heading
Usage: Mandatory
Max Use: 1
Purpose: To indicate the start of a transaction set and to assign a control number
Syntax Notes:
Semantic Notes:
Comments: 1 The transaction set identifier (ST01) is intended for use by the translation routines of the interchange partners to select the appropriate transaction set definition (e.g., 810 selects the invoice transaction set).

Data Element Summary

	Ref.	Data	Attributes
	<u>Des.</u>	<u>Element</u> <u>Name</u>	
Must Use	ST01	143 Transaction Set Identifier Code	M ID 3/3
		Code uniquely identifying a Transaction Set	
		864 X12.34 Text Message	
Must Use	ST02	329 Transaction Set Control Number	M AN 4/9
		Identifying control number assigned by the originator for a transaction set.	

Segment: **BMG** Beginning Segment For Text Message
Position: 020
Loop:
Level: Heading
Usage: Mandatory
Max Use: 1
Purpose: To indicate the beginning of a Text Message Transaction Set
Syntax Notes:
Semantic Notes:
Comments: 1 BMG02 contains the message subject.

Data Element Summary

	<u>Ref.</u>	<u>Data</u>	<u>Name</u>	<u>Attributes</u>
	<u>Des.</u>	<u>Element</u>		
Must Use	BMG01	353	Transaction Set Purpose Code	M ID 2/2
			Code identifying purpose of transaction set	
			00 Original	
	BMG02	352	Description	O AN 1/80
			A free-form description to clarify the related data elements and their content	

Segment: **DTM** Date/Time/Period
Position: 030
Loop:
Level: Heading
Usage: Optional
Max Use: 10
Purpose: To specify pertinent dates and times
Syntax Notes: 1 At least one of DTM02 or DTM03 is required.
Semantic Notes:
Comments:

Data Element Summary

	<u>Ref.</u>	<u>Data</u>	<u>Attributes</u>
	<u>Des.</u>	<u>Element</u> <u>Name</u>	
Must Use	DTM01	374 Date/Time Qualifier	M ID 3/3
		Code specifying type of date or time, or both date and time	
		097 Transaction Creation	
	DTM02	373 Date	C DT 6/6
		Date (YYMMDD)	
		<i>All dates specified herein employ the bridging (windowing or 49/50 rule) application.</i>	
Not Used	DTM03	337 Time	C TM 4/4
		Time expressed in 24-hour clock time (HHMMSS) (Time range: 000000 through 235959)	
Not Used	DTM04	623 Time Code	O ID 2/2
		Code identifying the time. In accordance with International Standards Organization standard 8601, time can be specified by a + or - and an indication in hours in relation to Universal Time Coordinate (UTC) time; since + is a restricted character, + and - are substituted by P and M in the codes that follow	
		Refer to 003010 Data Element Dictionary for acceptable code values.	

Segment: **N1** Name
Position: 040
Loop: N1 Optional
Level: Heading
Usage: Optional
Max Use: 1
Purpose: To identify a party by type of organization, name, and code
Syntax Notes:

- 1 At least one of N102 or N103 is required.
- 2 If either N103 or N104 is present, then the other is required.

Semantic Notes:
Comments:

- 1 This segment, used alone, provides the most efficient method of providing organizational identification. To obtain this efficiency the "ID Code" (N104) must provide a key to the table maintained by the transaction processing party.

Data Element Summary				
Ref.	Data			
<u>Des.</u>	<u>Element</u>	<u>Name</u>	<u>Attributes</u>	
Must Use	N101	98	Entity Identifier Code	M ID 2/2
			Code identifying an organizational entity or a physical location.	
		FR	Message From	
	N102	93	Name	C AN 1/35
			Free-form name	
	N103	66	Identification Code Qualifier	C ID 1/2
			Code designating the system/method of code structure used for Identification Code (67)	
		10	Department of Defense Activity Address Code (DODAAC)	
		33	Commercial and Government Entity (CAGE)	
		ZZ	Mutually Defined	
	N104	67	Identification Code	C ID 2/17
			Code identifying a party.	

Segment: **N3** Address Information
Position: 060
Loop: N1 Optional
Level: Heading
Usage: Optional
Max Use: 2
Purpose: To specify the location of the named party
Syntax Notes:
Semantic Notes:
Comments:

Data Element Summary				
	Ref.	Data		Attributes
	Des.	Element	Name	
Must Use	N301	166	Address Information	M AN 1/35
			Address information	
	N302	166	Address Information	O AN 1/35
			Address information	

Segment:	REF Reference Numbers
Position:	080
Loop:	N1 Optional
Level:	Heading
Usage:	Optional (Must Use)
Max Use:	12
Purpose:	To specify identifying numbers.
Syntax Notes:	1 At least one of REF02 or REF03 is required.
Semantic Notes:	
Comments:	
Notes:	<i>At least one iteration, with code 65 in REF01 is required to carry the Universal Tracking Number (UTN).</i>

Data Element Summary

	<u>Ref.</u> <u>Des.</u>	<u>Data</u> <u>Element</u>	<u>Name</u>	<u>Attributes</u>
Must Use	REF01	128	Reference Number Qualifier	M ID 2/2
			Code qualifying the Reference Number.	
			65 Total Order Cycle Number	
			<i>UTN- Universal Tracking Number is a unique identifier used to establish a linkage within a cycle of transaction sets for a single acquisition. Should be a unique identifier within Federal Agencies. A cycle is defined to include all related transaction sets (840, 843, 850, 855, 860, 865, 810 and 820 if possible).</i>	
			CT Contract Number	
			DX Department/Agency Number	
			IX Item Number	
			PO Purchase Order Number	
	REF02	127	Reference Number	C AN 1/30
			Reference number or identification number as defined for a particular Transaction Set, or as specified by the Reference Number Qualifier.	
	REF03	352	Description	C AN 1/80
			A free-form description to clarify the related data elements and their content	

Segment: **PER** Administrative Communications Contact

Position: 090

Loop: N1 Optional

Level: Heading

Usage: Optional

Max Use: 3

Purpose: To identify a person or office to whom administrative communications should be directed

Syntax Notes: 1 If PER03 is present, then PER04 is required.

Semantic Notes:

Comments:

Data Element Summary

	<u>Ref.</u>	<u>Data</u>	<u>Attributes</u>
	<u>Des.</u>	<u>Element</u> <u>Name</u>	
Must Use	PER01	366 Contact Function Code	M ID 2/2
		Code identifying the major duty or responsibility of the person or group named	
		IC Information Contact	
	PER02	93 Name	O AN 1/35
		Free-form name	
	PER03	365 Communication Number Qualifier	O ID 2/2
		Code identifying the type of communication number	
		EM Electronic Mail	
		FX Facsimile	
		TE Telephone	
	PER04	364 Communication Number	C AN 7/21
		Complete communications number including country or area code when applicable	

Segment: **MIT** Message Identification
Position: 010
Loop: MIT Mandatory
Level: Detail
Usage: Mandatory
Max Use: 1
Purpose: To identify the beginning of a specific message and to allow the identification of a subject for the message

Syntax Notes:**Semantic Notes:**

- Comments:**
- 1 MIT01 contains the message number.
 - 2 MIT02 contains the message subject.
 - 3 MIT03 default is 80 characters.
 - 4 MIT04 default is 66 lines.

Data Element Summary

	Ref. Des.	Data Element	Name	Attributes
Must Use	MIT01	127	Reference Number Reference number or identification number as defined for a particular Transaction Set, or as specified by the Reference Number Qualifier.	M AN 1/30
	MIT02	352	Description A free-form description to clarify the related data elements and their content	O AN 1/80
Not Used	MIT03	931	Page Width Definition of the maximum number of characters per line that can be expected in the message text	O N0 1/3
Not Used	MIT04	932	Page Length Lines Definition of the maximum number of lines per page that can be expected in the message text	O N0 1/3

Segment: **MSG** Message Text
Position: 080
Loop: MIT Mandatory
Level: Detail
Usage: Mandatory
Max Use: 100000
Purpose: To provide a free form format that would allow the transmission of text information.
Syntax Notes:
Semantic Notes:
Comments: 1 MSG02 is not related to the specific characteristics of a printer, but identifies top of page, advance a line, etc.

Data Element Summary

	<u>Ref.</u>	<u>Data</u>	<u>Attributes</u>
	<u>Des.</u>	<u>Element</u> <u>Name</u>	
Must Use	MSG01	933 Free-Form Message Text Free-form message text	M AN 1/264
Not Used	MSG02	934 Printer Carriage Control Code A field to be used for the control of the line feed of the receiving printer Refer to 003010 Data Element Dictionary for acceptable code values.	O ID 2/2

Segment: **SE** Transaction Set Trailer
Position: 010
Loop:
Level: Summary
Usage: Mandatory
Max Use: 1
Purpose: To indicate the end of the transaction set and provide the count of the transmitted segments (including the beginning (ST) and ending (SE) segments).

Syntax Notes:**Semantic Notes:**

Comments: 1 SE is the last segment of each transaction set.

Data Element Summary

	Ref.	Data		
	<u>Des.</u>	<u>Element</u>	<u>Name</u>	<u>Attributes</u>
Must Use	SE01	96	Number of Included Segments	M N0 1/6
			Total number of segments included in a transaction set including ST and SE segments	
Must Use	SE02	329	Transaction Set Control Number	M AN 4/9
			Identifying control number assigned by the originator for a transaction set.	